



Walk  
with  
confidence.

## Product Information

# 2" Safety Walk Teak Brown

<b>Product Code:</b>	<b>C2029</b>
<b>Product Family:</b>	Redistribution Products
<b>Manufacturer:</b>	Sure-Foot Industries Corp. 20260 First Ave. Cleveland, Ohio 44130
<b>Contact Info:</b>	Toll-Free Ph: 800-732-8289 Web: coreflooring.ca
<b>Origin:</b>	Imported from USA
<b>Section:</b>	09 65 00 Resilient Flooring
<b>Related Section:</b>	09 68 00 Carpeting
<b>Usage:</b>	A grit tape for stand-alone application or as an insert to treads.
<b>Physical Char:</b>	Paper Tape with Grit in an adhesive matrix.
<b>Dimensions:</b>	Heavy Grit Tape 2" x 60' Long
<b>Packaging:</b>	6 Rolls per Carton
<b>Colour Selection:</b>	N/A
<b>DSH:</b>	Store in original packaging until required for use.
<b>Conditions:</b>	Surface requiring tape should be clean and dry. Use appropriate Installation Guide for directions.
<b>Warranty:</b>	Limited 1 Year Warranty. Full details available on request.
<b>2-2-A Material:</b>	Paper/Adhesive/Grit
<b>2-2-B Physical Prop:</b>	Flexible Tape
<b>2-2-B-1 Recy Cont:</b>	None.
<b>2-2-B-2 Density:</b>	N/A
<b>2-2-B-3 Hardness:</b>	N/A
<b>2-2-B-6 Flame Spr Ind:</b>	ASTM E 84, Class B
<b>2-2-B-7 MRM:</b>	Resistant.
<b>2-2-B-8 Flexibility:</b>	N/A
<b>2-2-B-9 Direct Grade:</b>	
<b>2-2-B-10 Direct Masonry:</b>	

<b>2-2-B-11 Thermodynamic:</b>	
<b>2-2-B-12 Heat Forming:</b>	N/A
<b>2-2-B-13 Loading:</b>	Not load-bearing.
<b>2-2-B-14 Paintability:</b>	N/A
<b>2-2-B-15 Colourfastness:</b>	Colourfast.
<b>2-2-B-16 Environmental:</b>	SCS Global FloorScore Certified as part of Stair Treads/Nosings
<b>2-2-B-17 Flash Point:</b>	
<b>2-2-B-18 Ignition Conditions:</b>	Paper backing will burn in a fire.
<b>2-2-B-19 Extinction:</b>	Use appropriate means for surrounding materials.
<b>2-2-B-20 Reactivity:</b>	Adhesive may react with some surfaces over time.

## ***INSTALLATION INSTRUCTIONS***

### **Safety Walk Abrasive Tape**

<b><i>Introduction:</i></b>	Abrasive Tape can be installed as a grip aid on flooring surfaces, or installed on stair treads and some nosings where extra grip is desired. Available in four colours to provide a variety of looks; also in a fluorescent white (Night Glow) for a visibility aid.
<b><i>Handling and Storage:</i></b>	Leave in packaging until required for use.
<b><i>Subfloor Preparation:</i></b>	Surface of material receiving tape should be free of debris and dust - we recommend vacuuming/wiping dry before installation.
<b><i>Product Preparation:</i></b>	Cut required length before removing protective backing.
<b><i>Installation:</i></b>	Slowly remove backing from tape, pressing tape onto receiving surface and ensuring a straight, even application.  If questions arise that have not been addressed in this document, contact your local CORE Flooring Accessories distributor for assistance or CORE Flooring Customer Service at 1-800-732-8289.

## ***Maintenance Guide***

### **CORE Vinyl Stair Treads**

<b><i>Regular Maintenance:</i></b>	<ol style="list-style-type: none"> <li>1. Thoroughly sweep or vacuum the entire surface area to remove all loose dirt and grit.</li> <li>2. Prepare a cleaning solution by mixing 1 oz. to 4 oz. of neutral detergent (pH of 7-8) per gallon of warm water. The dilution depends on light to heavy soil conditions.</li> <li>3. Apply the solution with a clean nylon or rayon mop, and let stand for 5-10 minutes.</li> <li>4. Agitate the solution with a mop or a soft nylon deck brush, then wet vacuum or mop up the cleaning solution.</li> <li>5. Rinse stair treads with clean cold water then remove all water with a mop.</li> </ol>
------------------------------------	--

*Special Instructions:*

6. Allow the product to thoroughly dry.

Do not perform any maintenance on the products for 72 hours after installation is completed.

## *Warranty*

# Other Products

*Warranty Details:*

### DISTRIBUTED PRODUCTS LIMITED WARRANTY

For a period of one (1) year from the date of shipment, Grip-Rite Carpet Accessories Ltd. (Grip-Rite) makes the following warranty, subject to the terms and conditions specified herein, for all distributed products sold by Grip-Rite.

Products will conform to the Specifications description, with only such reasonable variations as is acceptable in the trade; it is fit for the ordinary purposes for which the product is used; and it will be adequately packaged and labeled.

Grip-Rite will replace any defective product at no charge if the defect is found prior to installation. If the customer believes the product to be defective after installation, the customer must promptly notify Grip-Rite and permit an inspection of the product. If, upon inspection, Grip-Rite determines the product to be defective, subject to the limitations contained in this warranty, Grip-Rite will replace the defective product at its cost.

To be eligible for replacement under any of these warranties, the customer must give Grip-Rite written notice of any claimed defect immediately upon learning of the defect and in no event more than 90 days after the claimed defect is discovered. Notice shall be given to Grip-Rite at its Corporate Address of 12002 – 75th Street, Edmonton, Alberta T5B 2B6.

#### Excluded from Warranty

These warranties do not apply to the following:

1. Any express or implied promise made by any salesman or representative that exceed the limits of these warranties.
2. Tears, burns, cuts, or other damage due to improper installation, improper use of cleaning agents, or of improper maintenance methods.
3. Labor costs for installation of original or replacement material.
4. Sale of "Seconds", "Off Goods" or other irregular (non-first-quality) flooring materials. With respect to "Seconds" or "Off Goods", such are sold "as is", and Grip-Rite makes no warranties whatsoever, express or implied with respect thereto, including warranties of merchantability or fitness for a particular purpose.
5. Problems caused by moisture, hydrostatic pressure, or alkali in the sub-floor.
6. Problems caused by uses, maintenance and installation that are contrary to Grip-Rite's specifications, recommendations or instructions.
7. Material installed with obvious defects.
8. Damage to flooring products from high heels or spike heels.
9. Installation of Grip-Rite products with adhesives or fasteners other than

those recommended by Grip-Rite.

10. Exterior installations. Grip-Rite's products are designed for interior applications only.

11. Fading and/or discoloration resulting from heavy sunlight penetration and ultraviolet ray exposure from direct or glass-filtered sunlight.

12. Material that is not installed and maintained as recommended by Grip-Rite.

13. Damage to flooring products from pallet jacks, construction carts, motorized traffic, or the moving of furniture.

14. Premature wear and deterioration from furniture, spikes, or skate blade exposure.

15. Differences in colour between products and printed or electronic images.

17. Embossing deviations between product and samples, photography and printed colour illustrations.